

756 III / 757 III





756 III: black silicone strap. ø 40 mm (Fig.: 1:1)



756 III: black leather strap.ø40 mm (Fig.: 1:1)



757 III: fine-link bracelet.ø43 mm (Fig.: 1:1)



757 III: back view. ø 43 mm (Fig.: 1:1)



756 III: luminous. ø 40 mm (Fig.: 1:1)



757 III: luminous.ø43 mm (Fig.: 1:1)

Large picture on the front: **756 III**: fine-link bracelet. **757 III**: black leather strap with integrated case.

756 III / 757 III

Limited edition each to 75 units Case made of stainless steel, satinized Case made with TEGIMENT Technology and therefore especially scratch-resistant Nickel-free case back without TEGIMENT Technology Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging Magnetic Field Protection up to 80,000 A/m Functionally reliable from – 45 °C up to + 80 °C Sapphire crystal glass Pressure-resistant to 20 bar Low pressure resistant 757 III: Captive pilot's bezel with minute ratcheting

The 756 and 757 series feature a striking design, contrasting displays and clear readability.

We have developed a special, new colour scheme for the 756 III and 757 III editions, which are limited to each 75 units. High-contrast, matt colours with a glossy, fine-satinised, stainless-steel case and sapphire crystal. The white hour indices and the 3, 6, 9 and 12 hour counters against the dark-blue dial ensure optimal readability. The chronograph hands and minutes stand out in orange, while warm-grey counters accentuate the striking face of these duochronographs.

The range of technologies in the watches includes Magnetic Field Protection up to 80,000 A/m, Ar-Dehumidifying Technology for increased functional reliability and freedom from fogging, Temperature Resistance Technology for reliable function in temperatures of – 45 °C to + 80 °C, and a highly scratchproof case based on TEGIMENT Technology. The watches are also resistant to low pressure and pressure-resistant to 20 bar.