

756

The Duochronograph.

- Case made of stainless steel, bead-blasted
- Case made with TEGIMENT Technology and therefore especially scratch-resistant
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 80,000 A/m
- Functionally reliable from -45°C up to +80°C
- Sapphire crystal glass
- Nickel-free case back without TEGIMENT Technology
- Pressure-resistant to 20 bar
- Low pressure resistant
-

The 756 series pilot's watches unite all our core watchmaking competencies: these are instrument watches with a consistently functional design which honour the tradition of our navigation cockpit clocks. The features of the 756 chronographs series include Magnetic Field Protection of up to 80,000 A/m, Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging, TEGIMENT Technology and therefore especially scratch-resistant, functionally reliable from -45°C up to +80°C and pressure resistance of up to 20 bar.



SINN SPEZIALUHREN GMBH

Technical details

Mechanical Movement

The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information.

- Valjoux 7750
- Self-winding mechanism
- 25 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Anti-magnetic as per DIN 8309

Case

- Case made of stainless steel, bead-blasted
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened, nickel-free
- Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Pressure-resistant up to 20 bar
- Low pressure resistant

Functions

- Hours, minutes
- Date display
- Chronograph

SINN SPEZIALUHREN GMBH

SINN Technologies

- TEGIMENT Technology, therefore especially scratch-resistant
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature resistance technology, therefore functionally reliable at temperatures from -45 °C up to +80°C
- Magnetic Field Protection up to 80,000 A/m
- Push-pieces with D3-System

Dimensions and Weight

- Case diameter: 40 mm
- Band lug width: 20 mm
- Case thickness: 14 mm
- Weight without strap: 91 gramme

Dial and Hands

- Matte black dial
- Number "12" and indices coated with luminescent colour
- Hour, minute hand coated with luminescent colour

SINN SPEZIALUHREN GMBH

Wilhelm-Fay-Straße 21 • 65936 Frankfurt am Main • Tel. +49 (0)69 978414-0 • Fax +49 (0)69 978414-201 • info@sinn.de • www.sinn.de

Managing director: Lothar Schmidt • District court Frankfurt am Main • HRB 38841 • VAT identification number: DE249383321 • WEEE-REg.-Nr.: DE75393444