

857 UTC TESTAF

The TESTAF-certified pilot watch designed for professional use.

- Tested and certified to the Technical Standard for Pilot Watches (TESTAF) by the Aachen University of Applied Sciences
- Second time zone on a 24-hour basis
- Case made of stainless steel, bead-blasted
- Case made with TEGIMENT Technology and therefore especially scratch-resistant
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Functionally reliable from -45°C up to $+80^{\circ}\text{C}$
- Captive pilot's bezel with minute ratcheting
- Sapphire crystal glass
- Pressure-resistant to 20 bar
- Low pressure resistant
-



The 857 UTC TESTAF was tested and certified to the the "Technical Standard for Pilot Watches" (Technischer Standard Fliegeruhren – TESTAF) by the Aachen University of Applied Sciences. This establishes its suitability for professional use as a pilot watch. It is attested to by a certificate and the "TESTAF" quality seal on the dial. The case of the 857 UTC TESTAF has been hardened with TEGIMENT Technology to make it especially scratch-resistant. The range of technologies also includes Ar-Dehumidifying Technology for greater functional reliability and freedom from fogging and overall functional reliability at temperatures between -45°C and $+80^{\circ}\text{C}$. The 857 UTC TESTAF features a further time measurement element: a display for a second time zone on a 24-hour basis.

SINN SPEZIALUHREN GMBH

Wilhelm-Fay-Straße 21 • 65936 Frankfurt am Main • Tel. +49 (0)69 978414-0 • Fax +49 (0)69 978414-201 • info@sinn.de • www.sinn.de

Managing director: Lothar Schmidt • District court Frankfurt am Main • HRB 38841 • VAT identification number: DE249383321 • WEEE-Reg.-Nr.: DE75393444

Technical details

Mechanical Movement

The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information.

- ETA 2893-2
- Self-winding mechanism
- 21 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Shock resistant as per DIN ISO 1413
- Anti-magnetic as per DIN 8309

Case

- Case made of stainless steel, bead-blasted
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened
- Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Pressure-resistant up to 20 bar
- Low pressure resistant

Functions

- Hours, minutes, seconds
- Second time zone on a 24-hour basis
- Date display
- Pilot's bezel with minute ratcheting and luminous key mark

SINN SPEZIALUHREN GMBH

SINN Technologies

- TEGIMENT Technology, therefore especially scratch-resistant
- Captive bezel
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature resistance technology, therefore functionally reliable at temperatures from minus 45°C up to 80°C

Dimensions and Weight

- Case diameter: 43 mm
- Band lug width: 22 mm
- Case thickness: 12 mm
- Weight without strap: 90 gramme

Dial and Hands

- Matte black dial
- Numbers and indices coated with luminescent colour
- Hour, minute and second hand coated with luminescent colour

SINN SPEZIALUHREN GMBH