

900 PILOT S

The large pilot chronograph.

- Case made of stainless steel
- Case made with Black Hard Coating on a TEGIMENT Technology basis
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 80,000 A/m
- Sapphire crystal glass
- Nickel-free case back without TEGIMENT Technology
- Interior pilot's bezel
- Second time zone on a 24-hour basis
- Appliqués meticulously attached by hand
- Waterproof and pressure-resistant to 20 bar
- Low pressure resistant
-



Black signifies objectivity and functionality – both of which are inherent in the design of the 900 PILOT S pilot watch. But there is a further connection to the colour black: the S in the model name stands for “Schwarz” (black) – signifying the black hard coating of the watch. There is an overriding SINN priority behind this – the suitability of each watch for everyday use. To achieve this we have additionally hardened the satinised stainless steel case using TEGIMENT Technology. The hardening also provides the base to which the high-grade, black PVD coating can be applied. This combined process results in a highly practical benefit: by applying a hard coating to the hardened steel, we prevent the otherwise common problem of cracking paint.

The pilot watch's other technical features also fulfil the most exacting demands in terms of precision and functionality. The black dial and the case diameter of 44 mm ensure perfect readability, for instance. Crucial features for professional use include Magnetic Field Protection up to 80,000 A/m, the interior pilot's bezel which can easily be set using the knurled crown at 10 o'clock and the second time zone on 24-hour basis.

SINN SPEZIALUHREN GMBH

Wilhelm-Fay-Straße 21 • 65936 Frankfurt am Main • Tel. +49 (0)69 978414-0 • Fax +49 (0)69 978414-201 • info@sinn.de • www.sinn.de

Managing director: Lothar Schmidt • District court Frankfurt am Main • HRB 38841 • VAT identification number: DE249383321 • WEEE-Reg.-Nr.: DE75393444

Technical details

Mechanical Movement

The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information.

- SW 500
- Self-winding mechanism
- 25 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Anti-magnetic as per DIN 8309

Case

- Case made of stainless steel, black
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened, nickel-free
- Winding crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Waterproof and pressure-resistant to 20 bar
- Low pressure resistant

Functions

- Hours, minutes, subsidiary seconds
- Second time zone on a 24-hour basis
- Date display
- Chronograph
- Interior pilot's bezel with luminous key mark

SINN SPEZIALUHREN GMBH

SINN Technologies

- Black Hard Coating on a TEGIMENT Technology basis
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 80,000 A/m
- Push-pieces with D3-System

Dimensions and Weight

- Case diameter: 44 mm
- Band lug width: 22 mm
- Case thickness: 15.5 mm
- Weight without strap: 103 gramme

Dial and Hands

- Black electroplated dial
- Appliqués meticulously attached by hand
- Appliqués and key mark luminescent
- Hour and minute hand coated with luminescent colour

SINN SPEZIALUHREN GMBH