

U2 C

The mission timer for divers made of German Submarine Steel with Black Hard Coating.

- Exclusive special edition for the specialist watch magazine *Chronos*
- Limited to 50 pieces
- Completely made of high-strength seawater-resistant German Submarine Steel
- Tested based on European diving equipment standards and certified by DNV GL
- Black Hard Coating on a TEGIMENT Technology basis
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Functionally reliable from -45°C up to $+80^{\circ}\text{C}$
- Captive diver's bezel with minute ratcheting
- Crown at 4 o'clock to prevent pressure on the back of the hand
- Mission timer design for optimal readability
- Sapphire crystal glass
- Pressure-resistant to 2,000 m diving depth (200 bar), certified by DNV GL
- Low pressure resistant



In collaboration with the specialist watch magazine *Chronos* published by Ebner Verlag, we are presenting a special limited edition of 50 U2 C models in a highly unique, technical and masculine design. For example, the mission timer is made of high-strength, seawater-resistant German submarine steel in a unique colour design with anthracite and grey accents. The watch comes with a matching grey-and-black textile strap and an olive-green silicone strap with an expandable folding safety clasp as standard. This allows you to swap and change the strap on this exceptional diver's watch to suit the occasion or purpose. The technologies used make the U2 C a robust and accurate instrument for professional diving. For example, Ar-Dehumidifying Technology ensures greater functional reliability and freedom from fogging. Temperature Resistance Technology guarantees the functional reliability of the watch in temperatures ranging from -45°C to $+80^{\circ}\text{C}$. The surface of the case has also been hardened using TEGIMENT Technology, making it especially scratch-resistant. This TEGIMENT surface provides the base for the high-quality Black Hard Coating (PVD coating). The classification company

SINN SPEZIALUHREN GMBH

DNV GL has tested the reliability and suitability of the watch for professional use. It verifies and certifies the pressure resistance of the U2 C to a diving depth of 2,000 metres (= 200 bar) and temperature resistance and functionality in accordance with the European diving device standards. What makes the U2 C of special value to watch lovers is the fact that it is limited to just 50 pieces. The U2 C comes with the aforementioned two straps, a band replacement tool, spare spring bars and a care cloth.

SINN SPEZIALUHREN GMBH

Wilhelm-Fay-Straße 21 • 65936 Frankfurt am Main • Tel. +49 (0)69 978414-0 • Fax +49 (0)69 978414-201 • info@sinn.de • www.sinn.de

Managing director: Lothar Schmidt • District court Frankfurt am Main • HRB 38841 • VAT identification number: DE249383321 • WEEE-REg.-Nr.: DE75393444

Technical details

Mechanical Movement

The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information.

- ETA 2892-A2
- Self-winding mechanism
- 21 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Shock resistant as per DIN ISO 1413
- Anti-magnetic as per DIN 8309

Case

- Case made of German Submarine Steel, black
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened
- Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Pressure-resistant up to 200 bar, certified by DNV GL
- According to the technical demands for the diving norm DIN 8306
- Tested based on European diving equipment standards EN 250 / EN14143 and certified by DNV GL
- Low pressure resistant

Functions

- Hours, minutes, seconds
- Date display
- Diver's bezel with minute ratcheting and luminous key mark

SINN SPEZIALUHREN GMBH

SINN Technologies

- Black Hard Coating on a TEGIMENT Technology basis
- Captive bezel
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature Resistance Technology, therefore functionally reliable at temperatures from -45°C up to +80°C

Dimensions and Weight

- Case diameter: 44 mm
- Band lug width: 22 mm
- Case thickness: 15.5 mm
- Weight without strap: 114 gramme

Dial and Hands

- Matte black dial
- Indices coated with luminescent colour
- Hour, minute and second hand coated with luminescent colour

SINN SPEZIALUHREN GMBH